

### 1" Wide Eye-To-Eye Lifting Slings



Orange color to designate quality and promote visual awareness

All slings have red core safety yarns that become visible when the outer layers are worn, providing a signal that the sling should be removed from service

Wear pad to increase sling life

Heavy-duty tag designed to stay attached for the life of the sling

3" and 4" wide slings have tapered eyes for ease of use

#### Specification:

- 1" width
- Available in lengths from 3' to 10'
- Polyester construction
- Proudly made in the USA

## SPECIFICATION SHEET

# 1" Wide Eye-To-Eye Lifting Slings

### Rated Capacity in Pounds

WEB WIDTH	VERTICAL	CHOKER	BASKET	60° ANGLE	45° ANGLE	30° ANGLE
1"	3,200	2,500	6,400	5,500	4,500	3,200

#### ALWAYS

- Store and handle webbing slings correctly.
- Inspect slings and accessories before use and before placing in storage.
- Position the bight for choke lift at 120 (natural angle).
- Position the sling so that the load is uniformly spread over its width and protect the sling from sharp edges.
- Apply the correct mode factor for the slinging arrangement.

#### NEVER

- Attempt to shorten, tie or knot webbing slings
- Expose webbing slings to direct heat or flames
- Expose webbing slings to chemicals without consulting the supplier
- Shock load webbing slings
- Use webbing slings which are cut or have loose or damaged stitching
- Use a sling with missing/damaged label or illegible markings

#### IN - SERVICE INSPECTION AND MAINTENANCE

Maintenance requirements are minimal. Webbing slings may be cleaned with clear water. Remember weak chemical solutions will become increasingly stronger by evaporation. Before each use inspect webbing slings and in the event of the following defects, refer the sling to a competent person for thorough examination: illegible markings; damaged, chafed or cut webbing; damaged or loose stitching; heat damage; burns; chemical damage; solar degradation; damaged or deformed end fittings



\*\* Warning! Failure to follow proper care, use and inspection criteria may result in personal injury. Do not exceed rated capacities. Horizontal sling angles less than 30° shall not be used.

SKU	DESCRIPTION	UOM
42951	1" x 3' Sling	ea
42492	1" x 4' Sling	ea
42493	1" x 6' Sling	ea
42494	1" x 8' Sling	ea
42495	1" x 10' Sling	ea

800.451.5811 | powerpak.net | 225 N Rte 303 Unit 108 | Congers, NY 10920

© 2021 PowerPak® Civil & Safety | All Rights Reserved