



## CONTRACTOR GRADE

# ORANGE SILT FENCE - 36" X 100'

Contractor Grade Silt Fence by PowerPak is used in sloping and weak soil surfaces to prevent erosion and runoff. It is made from durable MISF150 fabric that gives it high grab tensile strength while exhibiting resistance to puncture, wear and tear.

**Hardwood Stakes Every 10':**

- Equipped with nominal 1" x 1" x 48" hardwood stakes every 10' amounting to a total of 11 such posts in the pack.

**UV Resistance ASTM D4355 80:**

- The geotextile is UV resistant and retains 80% of its strength after being exposed to UV rays for 500 hours.

**High Mullen Burst Strength ASTM D3786 325:**

- The silt barrier displays high Mullen burst strength of 325 lb, making it suitable for difficult outdoor conditions.

**Durability:**

- This durable silt fence has passed the ASTM 6461 testing. It has a flow rate permittivity of 30 gpm/sq.ft (ASTM D4491 30).

**ASTM Standards:**

- Grab Tensile Strength (lbs) - ASTM D4632 90
- Grab Tensile Elongation (%) - ASTM D4632 15
- Puncture Strength (lbs) - ASTM D4833 60
- Trapezoidal Tear (lbs) - ASTM D4632 90
- Apparent Opening (US Std Sieve) - ASTM D4632 15

