



Solvent-Based Marking Paint

A fast drying marking paint designed to be sprayed in an inverted position. Produces vivid marks, does not clog, and is safe for grass. The solvent based formulation works well in low temperatures. Meets APWA color standards and is VOC compliant.

Suggested Uses:

Utility marking	Construction sites
Golf courses	Surveying
Landscaping	Mining

Packaging:

Cans per case.....	12
Shipping weight per case.....	20 lbs.
Container.....	20 fluid ounce can
Label weight	17 ounces (482 grams)
Shipping Classification.....	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 500 linear feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point.....	-4F
Specific Gravity.....	0.80
Solids Content.....	36%
MIR value	0.82, cannot exceed 0.85
HAPs content	0
Storage Temperature	40-90F
Application Temperature	50-100F
Resin System.....	V.T. Alkyd
Shelf life.....	Guaranteed for 2 years

Dry Time*:

To touch	5 minutes @ 72F
.....	15 minutes@ 35F

Curing/Recoat time is extended with multiple coats and excessively thick coats

Gloss*.....Flat, <15

*as measured on a 60 degree gloss meter

Available Colors:

Color	Item#	Color	Item#
Blue.....	42686	Red.....	42692
Clear.....	42688	White.....	42693
Green	42689	Yellow.....	42694
Hi-Vis Orange.....	42690	Silver.....	42695
Pink.....	42691		

