



Water-Based Marking Paint

A fast drying marking paint designed to be sprayed in an inverted position. Uses a patented technology to cut the environmental impact in half (as compared to a standard solvent based marking paint). Produces vivid marks, does not clog, and is safe for grass. Meets APWA color standards.

Suggested Uses:

Utility marking	Construction sites
Golf courses	Surveying
Landscaping	Mining

Packaging:

Cans per case.....	12
Shipping weight per case.....	20 lbs.
Container.....	20 fluid ounce can
Label weight	17 ounces (454 grams)
Shipping Classification.....	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 500 linear feet
Cleanup	Paint or lacquer thinner
Flammability	Flammable
Flash point.....	-4F
Specific Gravity.....	0.73
Solids Content.....	16%
MIR value	0.48, cannot exceed 0.85
HAPs content	<1%
Storage Temperature	40-100F
Application Temperature	50-90F
Resin System.....	V.T. Alkyd
Shelf life.....	Guaranteed for 2 years
Freeze/Thaw Up to 7 times without harm	

****Do not warehouse in subfreezing temperatures****

Dry Time*:

To touch 15 minutes

*At 72F, 50% humidity, 1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

Gloss* :..... Flat, <15

*as measured on a 60 degree gloss meter

Available Colors:

Color	Item#	Color	Item#
Blue	42696	Red.....	42701
Black	42697	White.....	42702
Green	42698	Yellow.....	42703
Hi-Vis Orange.....	42699		
Pink.....	42700		

