

## Features

- Available in 2", 3" and 4" widths
- Manufactured with 2-ply Nylon
- Proudly made in the USA

### CODE DESCRIPTION

#### 1 INCH SLINGS

- 42492 1" x 4' Sling
- 42493 1" x 6' Sling
- 42494 1" x 8' Sling
- 42495 1" x 10' Sling

#### 2 INCH SLINGS

- 41312 2" x 4 Sling
- 41313 2" x 6 Sling
- 41314 2" x 8 Sling
- 41315 2" x 10 Sling
- 41316 2" x 12 Sling
- 42281 2" x 14 Sling
- 42203 2" x 15 Sling
- 41317 2" x 16 Sling
- 41318 2" x 20 Sling

#### 3 INCH SLINGS

- 41319 3" x 4 Sling
- 41320 3" x 6 Sling
- 42059 3" x 8 Sling
- 41322 3" x 10 Sling
- 41323 3" x 12 Sling
- 41321 3" x 14 Sling
- 41324 3" x 16 Sling
- 41325 3" x 20 Sling

#### 4 INCH SLINGS

- 41326 4" x 4 Sling
- 41327 4" x 6 Sling
- 41328 4" x 8 Sling
- 41329 4" x 10 Sling
- 41330 4" x 12 Sling
- 42202 4" x 14 Sling
- 41331 4" x 16 Sling
- 42434 4" x 18 Sling
- 41332 4" x 20 Sling

# Eye to Eye Lifting Slings



Rated Capacity in Pounds

WEB WIDTH	VERTICAL	CHOKER	BASKET
1"	3,200	2,500	6,400
2"	6,400	5,000	12,800
3"	8,900	7,200	17,800
4"	12,000	9,600	24,000

WEB WIDTH	60° ANGLE	45° ANGLE	30° ANGLE
1"	5,500	4,500	3,200
2"	11,100	9,000	6,400
3"	15,400	12,600	8,900
4"	20,800	17,000	12,000



**\*\*Warning!** Failure to follow proper care, use and inspection criteria may result in personal injury. Do not exceed rated capacities. Horizontal sling angles less than 30° shall not be used.

